

TANDEM VIBRATORY ROLLERS | CT160 / 260 / 380 / 430

JCB

**EASY
— IN A —
HARD WORLD**



OPERATING WEIGHT
1,710 - 4,500kg

ENGINE POWER
14.2 - 36.5kW

DRUM WIDTH
800 - 1,400mm

EASY TO BE PRODUCTIVE.

The CT range of tandem rollers feature high centrifugal forces and static linear loads for the best performance – dynamically or statically – on aggregates or asphalt.



PROVEN PERFORMANCE

The simple drum offset increases the efficiency and the chamfered drum edges create a smooth finish. The pressurised water sprinkler with upward facing nozzles ensures sufficient water supply on the drums.

EASY AND EFFICIENT.

The JCB CT tandem rollers have been designed to be easy to use, easy to be productive, easy to keep safe and secure and easy to service.



BUILT FOR EFFICIENCY

Our CT range all feature EU Stage V and EPA T4F engines. The CT160 & 260 feature a Kubota engine, whereas the CT380 & 430 use a Kohler engine.

EASY TO USE.

With a simple, intuitive control layout and superior operator comfort, our new tandem rollers make working not just easy but also a pleasure.



EASY TO CONTROL

A responsive directional drive lever makes for smooth operation, while our CT control panel has easy to understand work modes and easy to use switches.



EASY TO SERVICE.

Easy access engine service points, longer service intervals and many zero maintenance parts, our tandem rollers are easy to maintain.



EASY TO ACCESS

The well-protected radiator position at the centre of the machine makes it easy to clean and creates easy access to the battery and service points.

EASY TO KEEP SAFE AND SECURE.

With JCB's LiveLink telematics system as standard, plus many built-in safety features, the new CT tandem rollers give you complete peace of mind.



SAFE TO USE

The operator-present seat switch provides safety when mobile but has a timed cut-out delay, which still allows free movement on the seat.



TANDEM VIBRATORY ROLLERS | CT160 / 260 / 380 / 430



SPECIFICATION.

MODEL		CT160	CT260	CT380	CT430
Operating weight	kg	1,710 - 1,790	2,420 - 2,560	4,100	4,500
Drum width	cm	80 - 100	100 - 120	130	140
Static linear load (front/rear)	kg / cm	8.4 - 11.4	10.5 - 12.3	15.8	16.4
Engine power	kW	14.2	18.2	36.5	36.5
Frequency	Hz	50 - 66	50 - 66	50 - 60	50 - 60
Centrifugal force	kN	10.0 - 19.1	23.6 - 41.1	41 - 59	44 - 63



FITTED AS STANDARD

DAILY CHECKS	7 of 7
COOLANT LEVEL	<input checked="" type="checkbox"/> <input checked="" type="checkbox"/>
WASHER BOTTLE	<input checked="" type="checkbox"/> <input checked="" type="checkbox"/>
BRAKE RESERVOIR	<input checked="" type="checkbox"/> <input checked="" type="checkbox"/>
FUEL	<input checked="" type="checkbox"/> <input checked="" type="checkbox"/>
DEF	<input checked="" type="checkbox"/> <input checked="" type="checkbox"/>
BODYWORK & GLAZING	<input checked="" type="checkbox"/> <input checked="" type="checkbox"/>
TYRE/TRACK CONDITION	<input checked="" type="checkbox"/> <input checked="" type="checkbox"/>



LWE-1209-2108
001238763

2 Health 1 Failed check



STANDARD FEATURES.

- 2 Year LiveLink telematic contract
- Maintenance free centre joint
- High visibility tapered front frame
- EU Stage V & EPA T4F compliant engine
- Upward facing spray nozzles
- Simple and intuitive control layout
- Integrated vandal cover
- Automatic vibration control
- 56 / 60mm (CT160 / 260) and 80mm (CT380 / 430) drum offset



EASY IN A HARD WORLD.

FIND OUT MORE

REQUEST A QUOTE

 **JCB**

www.jcb.com

